## Introduction

The MM-EP15 is the 15” single pole for multi-monitor mounts with base for extrusion track installation. The MM-EP28 is the 28” version, and the MM-EP42 is the 42” version. These three different pole sizes provide more mounting options for those installing multi-monitor mounts. The larger the pole, the more displays that can be mounted per single base. This base is designed for extrusion tracks typically used on consoles for central stations and control centers. The extrusion base fits standard tracks and is a great mounting option for upgrading from traditional CRT monitors to HD flat-panel consoles.




## Parts List




MM-EP15/28/42
(Varied sized pole with extrusion base)
(Qty 1)



T-Nut
(Qty 4)



1/4-20” x 5/8” Flat Hex Screw
(Qty 4)

5/32” Hex Key
(Qty 1)

## Step 1

Multi-monitor mounts with extrusion track bases can be installed on 1.5” on center T slot channel or single T slot channel (channel not included).

First, determine where you would like your multi-monitor mount positioned on your desired surface. The mounting surface should be capable of supporing 5x the weight of the flat-panel and mount. (Mount and flat-panel sold separately)

Are you installing your pole on a 1.5” on center T slott channel?

If no, procede to step 2...
If yes, follow instructions below

1. For dual 1.5” on center channel you will need to use the four outer holes on the base of the pole (Figure 1)
2. Insert the four (4) 1/4 20” Flat Hex Screws through the top of the four holes on base shown in figure 1.
3. Thread the four (4) provided T nuts onto the bottom of each of the now installed screws (Figure 3).
   Do not thread all the way to the top.You will need to leave loose for positioning the tube on the extrusion track.

Procede to step 3.




(Figure 1)



(Figure 2)



(Figure 3)

## Step 2

For single T slot channel you will need to use the two center holes on the base of the pole (Figure 4).

Follow sub-steps 2 and 3 from the above section, but only use two (2) 1/4 20” Flat Hex Screw and two (2) T nuts into the holes noted in figure 4.

Procede to Step 3.




(Figure 4)

## Step 3

1. Once you have your Flat Hex Screws installed and T-Nuts threaded in, insert the base into the track.
2. The bottom cable routing hole should always be facing to the back.
3. Slide pole to the desired position on the track.
4. Once in place, tighten the (4 for the dual track and 2 for the single) 1/4 20” Flat Hex Screws with the included hex key so that the pole remains in place and is sturdy (Figure 5).
5. If the pole needs to be re-positioned on the track, loosen the the flat hex screws and simply slide to the new position. Repeat sub-step 3 in this section.



Single T Slot Channel



1.5” on Center T Slott Channel



(Figure 5)



PREMIER MOUNTS®
CREATING POSITIVE CUSTOMER EXPERIENCES
3100 E. Miraloma Avenue, Anaheim, CA 92806 | 800.368.9700 USA | F 800.832.4888 | www.mounts.com
Unit 3, The Moorings Business Park, Channel Way | Longford, Conventry, CV6 6RH, UK | +44 (0) 2476 644105 | F +44 (0) 2476 644165

**PREMIER MOUNTS**

**LIMITED LIFETIME WARRANTY**

**What and Who is Covered by this Limited Warranty and for How Long**
Premier Mounts warrants this product to be free from defects in material and workmanship for the lifetime of the original owner of this product. The limited warranty is valid only for the original purchaser of the product.

**What Premier Mounts Will Do**
At the sole option of Premier Mounts, Premier Mounts will repair or replace any product or product part that is defective. If Premier Mounts chooses to replace a defective product or part, a replacement product or part will be shipped to you at no charge, but you must pay any labor costs.

**What is Not Covered; Limitations**
PREMIER MOUNTS DISCLAIMS ANY LIABILITY FOR DAMAGE TO MOUNTS, ADAPTERS, DISPLAYS, PROJECTORS, OTHER PROPERTY, OR PERSONAL INJURY RESULTING, IN WHOLE OR IN PART, FROM IMPROPER INSTALLATION, MODIFICATION, USE OR MISUSE OF ITS PRODUCTS.
PREMIER MOUNTS DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. PREMIER MOUNTS IS NOT RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING BUT NOT LIMITED TO, INABILITY TO USE ITS PRODUCTS OR LABOR COSTS FOR REMOVING AND REPLACING DEFECTIVE PRODUCTS OR PARTS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR
CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

**What Customers Must Do for Limited Warranty Service**
If you discover a problem that you think may be covered by the warranty you MUST REPORT it in writing to the address below within thirty (30) days. Proof of purchase (an original sales receipt) from the original consumer purchaser must accompany all warranty claims. Warranty claims must also include a description of the problem, the purchaser's name, address, and telephone number. General inquiries can be addressed to Premier Mounts Customer Service at 1-800-368-9700. Warranty claims will not be accepted over the phone or by fax.

Premier Mounts
Attn: Warranty Claim
3130 East Miraloma Ave.
Anaheim, CA 92806

**How State Law Applies**
THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.


3100 E. Miraloma Avenue, Anaheim, CA 92806 | 800.368.9700 USA | F 800.832.4888 | www.mounts.com
Unit 3, The Moorings Business Park, Channel Way | Longford, Conventry, CV6 6RH, UK | +44 (0) 2476 644105 | F +44 (0) 2476 644165

## Introduction



The MM-A3 is a triple articulating multimonitor mount arm that works with any 2" tube. Each mounting head provides 90º of omnidirectional tilt. The mounting heads include both 75x75mm and 100x100mm VESA mounting patterns. The arm includes integrated cable management tabs to keep wires and cables protected and organized.

## Step 1

1. Slide your mounting arm over the pole and base (figure 1) (not included, but should be previously installed).

Determine the position on the pole desired for your mounting arm.

2. Once in desired position,tighten the two (2) pre-intalled M8 x 6mm set screws in the holes in the back of the MM-A3. Tighten with included allen key (Figure 2).



(Figure 1)



(Figure 2)

## Step 2

Are you installing to a 75x75mm or 100x100mm VESA moutning pattern?

For 75x75mm, use mounting points A. For 100x100mm use points B in figure 3.

1) Thread the M4 screws to one-half of their length into the top two mounting holes on each display, but do not tighten the M4 screws at this time.




(Figure 3)

## Parts List



MM-A3
Triple Articulating Mounting Arm
(Qty 1)

5/32" Allen Key
(Qty 1)



6mm Allen Key
(Qty 1)

M4 x 10mm Combo Screws
(Qty 12)

## Step 3

1) Insert the heads of the M4 screws through the keyhole slots on the mounting head (Figure 5).
2) Insert the remaining two (2) M4x10mm screws, into the bottom mounting points (Figure 4)
3) Repeat sub-steps 1 & 2 for the second and third display.
4) Tighten all M4 screws.

Do not overtighten the mounting hardware



(Figure 4)




Figure 5

## Step 3

To adjust the tension and/or tilt angle of the mounting head:

1) Adjust the mounting head by utilizing the 90° continuous tilt, until it is in the desired position.
2) Remove the side and bottom cosmetic caps from the mounting head (Figure 6)
3) Use the supplied 6mm allen wrench to tighten the allen screws on the head.
4) The side 6mm screw secures the tilt position (Point A), while the bottom 6mm screw secures the pivot (Point B).

Do not overtighten the mounting hardware




(Figure 6)
Bottom View



PREMIER MOUNTS®
CREATING POSITIVE CUSTOMER EXPERIENCES
3100 E. Miraloma Avenue, Anaheim, CA 92806 | 800.368.9700 USA | F 800.832.4888 | www.mounts.com
Unit 3, The Moorings Business Park, Channel Way | Longford, Conventry, CV6 6RH, UK | +44 (0) 2476 644105 | F +44 (0) 2476 644165

# PREMIER MOUNTS

## LIMITED LIFETIME WARRANTY

**What and Who is Covered by this Limited Warranty and for How Long**

Premier Mounts warrants this product to be free from defects in material and workmanship for the lifetime of the original owner of this product. The limited warranty is valid only for the original purchaser of the product.

**What Premier Mounts Will Do**

At the sole option of Premier Mounts, Premier Mounts will repair or replace any product or product part that is defective. If Premier Mounts chooses to replace a defective product or part, a replacement product or part will be shipped to you at no charge, but you must pay any labor costs.

**What is Not Covered; Limitations**

PREMIER MOUNTS DISCLAIMS ANY LIABILITY FOR DAMAGE TO MOUNTS, ADAPTERS, DISPLAYS, PROJECTORS, OTHER PROPERTY, OR PERSONAL INJURY RESULTING, IN WHOLE OR IN PART, FROM IMPROPER INSTALLATION, MODIFICATION, USE OR MISUSE OF ITS PRODUCTS.
PREMIER MOUNTS DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. PREMIER MOUNTS IS NOT RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING BUT NOT LIMITED TO, INABILITY TO USE ITS PRODUCTS OR LABOR COSTS FOR REMOVING AND REPLACING DEFECTIVE PRODUCTS OR PARTS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR
CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

**What Customers Must Do for Limited Warranty Service**

If you discover a problem that you think may be covered by the warranty you MUST REPORT it in writing to the address below within thirty (30) days. Proof of purchase (an original sales receipt) from the original consumer purchaser must accompany all warranty claims. Warranty claims must also include a description of the problem, the purchaser's name, address, and telephone number. General inquiries can be addressed to Premier Mounts Customer Service at 1-800-368-9700. Warranty claims will not be accepted over the phone or by fax.

Premier Mounts
Attn: Warranty Claim
3130 East Miraloma Ave.
Anaheim, CA 92806

**How State Law Applies**

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.


3100 E. Miraloma Avenue, Anaheim, CA 92806 | 800.368.9700 USA | F 800.832.4888 | www.mounts.com
Unit 3, The Moorings Business Park, Channel Way | Longford, Conventry, CV6 6RH, UK | +44 (0) 2476 644105 | F +44 (0) 2476 644165