


## INSTALLATION INSTRUCTIONS



### **SPI-EXT**

SpiroLock™ Universal Projector Mount With Extension

---

#### **NORTH AMERICA**

3130 East Miraloma Avenue  
Anaheim, CA 92806 USA  
USA and Canada  
Phone: 1.800.368.9700  
Fax: 1.800.832.4888  
Other Locations  
Phone: (001).714.632.7100  
Fax: (001).714.632.1044

---

#### **EUROPE**

Swallow House,  
Shilton Industrial Estate,  
Shilton, Coventry, England CV79JY  
Phone: +44 (0) 2476 614700  
Fax: +44 (0) 2476 614710



## Contents

Weight Limit.....	2
Warning Statements.....	2
Installation Tools.....	3
Parts List.....	3
Features.....	4
Installing the SpiroLock™ With Extension Mount.....	5
Introduction.....	5
Wood Stud Installation.....	6
Solid Ceiling Installation.....	7
Attaching the Projector Plate.....	9
Selecting the Mounting Hardware.....	9
Multiple Mounting Point Installation.....	9
Single Mounting Point Installation.....	12
Attaching the Projector to the Mount.....	12
Alignment & Fine-Tuning.....	13
Removing the Projector.....	14
Installing the Lock-It™ Security Barrel.....	15
Technical Specifications.....	15
Warranty.....	16
Disclaimer.....	16

## Weight Limit

Maximum Projector Weight: **45 lb.**

THE CEILING STRUCTURE MUST BE CAPABLE OF SUPPORTING AT LEAST FIVE TIMES THE WEIGHT OF THE PROJECTOR. IF NOT, THE CEILING STRUCTURE MUST BE REINFORCED.

## Warning Statements



PRIOR TO THE INSTALLATION OF THIS PRODUCT, THE INSTALLATION INSTRUCTIONS MUST BE READ AND COMPLETELY UNDERSTOOD. KEEP THESE INSTALLATION INSTRUCTIONS IN AN EASILY ACCESSIBLE LOCATION FOR FUTURE REFERENCE.



PROPER INSTALLATION PROCEDURE BY A QUALIFIED SERVICE TECHNICIAN MUST BE FOLLOWED, AS OUTLINED IN THESE INSTALLATION INSTRUCTIONS. FAILURE TO DO SO COULD RESULT IN PROPERTY DAMAGE, SERIOUS PERSONAL INJURY, OR EVEN DEATH.



SAFETY MEASURES MUST BE PRACTICED AT ALL TIMES DURING THE ASSEMBLY OF THIS PRODUCT. USE PROPER SAFETY EQUIPMENT AND TOOLS FOR THE ASSEMBLY PROCEDURE TO PREVENT PERSONAL INJURY.



PREMIER MOUNTS DOES NOT WARRANT AGAINST DAMAGE CAUSED BY THE USE OF ANY PREMIER MOUNTS PRODUCT FOR PURPOSES OTHER THAN THOSE FOR WHICH IT WAS DESIGNED OR DAMAGE CAUSED BY UNAUTHORIZED ATTACHMENTS OR MODIFICATIONS, AND IS NOT RESPONSIBLE FOR ANY DAMAGES, CLAIMS, DEMANDS, SUITS, ACTIONS OR CAUSES OF ACTION OF WHATEVER KIND RESULTING FROM, ARISING OUT OF OR IN ANY MANNER RELATING TO ANY SUCH USE, ATTACHMENTS OR MODIFICATIONS.



At least two qualified people should perform the assembly procedure. Personal injury and/or property damage can result from dropping or mishandling the projector.



If mounting to wall studs or ceiling studs, make sure that the mounting screws are anchored into the center of the wall studs or ceiling studs. Use of an edge-to-edge stud finder is recommended.



Be aware of the mounting environment. If drilling and/or cutting into the mounting surface, always make sure that there are no electrical wires in wall. Cutting or drilling into an electrical line may cause serious personal injury.



Make sure there are no water or natural gas lines inside the wall where the mount is to be located. Cutting or drilling into a water or gas line may cause severe property damage or personal injury.



This product is intended for indoor use only. Use of this product outdoors could lead to product failure and/or serious personal injury.



Do not install near sources of high heat. Do not install on a structure that is prone to vibration, movement or chance of impact.



Contact Premier Mounts with any questions:









(800) 368-9700

[techsupport@mounts.com](mailto:techsupport@mounts.com)


















## Installation Tools

The following tools may be required depending upon your particular installation. They are not included.

				
Electronic Stud Finder	Hand Held Drill	Pencil	Protective Eyewear	Phillips Tip Screwdriver
				
	Masonry Drill Bit	Ladder	1/8" Wood Drill Bit	

## Parts List

Make sure your Premier Mounts product has the following hardware and components before beginning installation. If there are parts missing and/or damaged, stop the installation and call Premier Mounts at (800) 368-9700.

SpiroLock™ With Extension Mount Hardware				
				
SpiroLock™ Projector Plate (Qty 1)		SpiroLock™ Ceiling Plate With Extension (Qty 1)		
				
#14 x 2" Wood Screws (Qty 2)	M5 Security Allen Wrench (Qty 1)	Mounting Legs (Qty 4)	M2.5 x 10mm Security Screw (Qty 4)	
				
M2.5 x 12mm Security Screw (Qty 4)	M3 x 16mm Security Screw (Qty 4)	M4 x 10mm Security Screw (Qty 4)	M4 x 12mm Security Screw (Qty 4)	
				
M5 x 12mm Security Screw (Qty 4)	M6 x 12mm Security Screw (Qty 8)	1/4-20 x 5/16" Security Screw (Qty 1)	M3 Flat Washer (Qty 10)	Lock-It™ Security Barrel (Qty 1)



## Features

The SpiroLock™ Universal Projector Mount is easy to install. Snap and lock the projector onto the mount, then rotate and pivot freely for the optimal viewing angle. The Lock-It™ security screws and leveling barrel add an extra layer of security and theft deterrence.

### Tool-Free Adjustment

Precise yaw, pitch and roll adjustments without requiring specialized tools.

### Locking Tab and Safety Screw

Assures that the projector plate releases only when you want it released.

### Radial Glide® Technology

Up to 6° of smooth adjustment in any direction.

### Mounting Slots

Allows you to choose from a variety of mounting options and projector mounting point configurations.

### Adjustable Leveling Barrels

You can quickly level the mounting legs without any specialized tools.

### Ceiling Plate

Can easily be installed on either a wood stud or solid ceiling.

### Mount Extension

Adds 11 to 15 inches to the mount's vertical adjustment.

### Lock-It™ Security Hardware


Protect your projector from theft by installing specialized hardware at critical mounting points.

### SpiroLock™ Installation

Torsion spring mechanism automatically twists and captures the SpiroLock™ projector plate.

### Mounting Legs

Combined with the numerous projector plate mounting slots, the mounting legs allow for multiple mount configurations.





## Installing the SpiroLock™ With Extension Mount

### Introduction

Your SpiroLock™ mount may be secured to either a single ceiling stud or a solid surface ceiling, such as concrete.

Please read these installation instructions once thoroughly before attempting to install your Premier Mounts product.


Please take a minute to familiarize yourself with the contents of the package and make sure you have all the parts and tools you need to safely complete the installation.

In addition, some steps of this installation may require two people to prevent personal injury and/or damage to your projector. Please observe all warnings in the following installation procedure and utilize proper safety equipment at all times.

Begin installing your SpiroLock™ mount by separating the ceiling plate from the projector plate.

### Step 1

Use the M5 Security Allen Wrench to loosen the M4 x 12mm Lock-It™ screw.



### Step 2

- ① Place one hand under the projector to support it.
- ② Lift the locking tab.
- ③ While lifting the locking tab, rotate the SpiroLock™ collar assembly 15 degrees clockwise until you hear an audible "click".



You may find it easier to lift the locking tab with the thumb of the same hand which rotates the SpiroLock™ collar assembly.


- ④ Use both hands to rotate the projector plate as shown to separate it from the SpiroLock™ collar assembly.



What type of ceiling are you installing to?

If you are installing your SpiroLock™ mount to a wood stud, proceed to **"Wood Stud Installation"** on page 6.

If you are installing your SpiroLock™ mount to a solid surface, such as a concrete ceiling, proceed to **"Solid Ceiling Installation"** on page 7.





## Installing the SpiroLock™ With Extension Mount (cont'd)


### Wood Stud Installation

#### Step 1

- 1 Use a stud finder to locate a ceiling stud closest to your desired installation location.
- 2 Identify the center of the ceiling stud.
- 3 Use a pencil to mark the location of the ceiling stud center.





The target arrow indicates the direction of the projector screen relative to the projector mount.



#### Step 2

- 1 Place the SpiroLock™ Ceiling Plate against the ceiling. Its mounting holes should align with the center of the ceiling stud.
- 2 Use a pencil and mark two (2) mounting hole locations through each of the mounting points (A) in the SpiroLock™ Ceiling Plate.



#### Step 3


- 1 Remove the SpiroLock™ Ceiling Plate and set it aside.
- 2 Drill a pilot hole in the center of each mark using a power drill and a 1/8" drill bit.

#### Pro Tip



##### Pilot Holes

When a screw is driven into a material, such as wood, it can act as a wedge, generating outward pressure which can cause many materials to split. Drilling a small pilot hole where the screw will be driven causes less 'wedging' to take place, thereby reducing the likelihood of the material being split. It also reduces the possibility of the screw head getting sheared off by torque.





## Installing the SpiroLock™ With Extension Mount (cont'd)


### Step 4

- ❶ Insert one (1) #14 x 2" screw through each of the mounting holes (A) on the bottom of the SpiroLock™ Ceiling Plate and into the pilot holes.
- ❷ Tighten each screw until the SpiroLock™ Ceiling Plate is secure against the ceiling.



Do not overtighten the #14 x 2" screws.


Proceed to the "Attaching the Projector Plate" section on page 9.



### Solid Ceiling Installation

Your SpiroLock™ projector mount can be mounted to any solid surface ceiling which has a minimum 6" thickness. Concrete wedge anchors must be used for concrete installation. It is recommended that ¼" wedge anchors be used. A masonry bit must be used to drill the pilot hole. Both wedge anchors and masonry drill bits are not supplied.

Continue on page 8.



Example Wedge Anchors and Masonry Bit  
Not included





## Installing the SpiroLock™ With Extension Mount (cont'd)

### Step 1

- 1 Place the SpiroLock™ Ceiling Plate into position against the ceiling.
- 2 Use a pencil and mark four (4) mounting hole locations through each of the mounting points (B) in the SpiroLock™ Ceiling Plate.



The target arrow indicates the direction of the projector screen relative to the projector mount.




### Step 2

- 1 Drill a hole at each mark using the appropriate diameter masonry bit for your wedge anchor.
- 2 Remove the nut and washer from the wedge anchors.
- 3 Insert a wedge anchor into each hole.



If necessary, a hammer can be used to lightly tap each wedge anchor into place.



### Step 3


- 1 Move the SpiroLock™ Ceiling Plate back into position.
- 2 Thread a wedge anchor nut (and washer, if provided with the wedge anchor) onto each threaded wedge anchor shaft.

Do not tighten any of the wedge anchor nuts (and any washers) until all nuts and washers are threaded onto the shafts.



Do not overtighten the wedge anchor nuts.

Proceed to the “Attaching the Projector Plate” section.







## Attaching the Projector Plate

### Selecting the Mounting Hardware

- ❶ Insert a small straw or toothpick into the threaded inserts found on the bottom or top of the projector.
- ❷ Use a pencil to mark the depth of the threaded insert on the small straw or toothpick.
- ❸ Mark the straw or toothpick 1/8" above the depth of the threaded insert, as shown in Figure 1.
- ❹ Insert the small straw or toothpick into the remaining threaded inserts to compare and verify their depth using the straw or toothpick's 1/8" allowance mark.
- ❺ Locate the correct diameter screw for the threaded insert.

**!** If the screw you selected is longer than the 1/8" allowance mark on the small straw or toothpick, as shown in Figure 2 and Figure 3, do not use this screw. The screw length must not bypass the mark.





- ❻ Test each size of the screws provided.

The correct screws should thread easily into the mounting point and not pull out when tension is applied.

- ?** Does your projector have a single mounting point or multiple mounting points?

If your projector has a single mounting point, skip to the **"Single Mounting Point Installation"** section on page 12.

If your projector has multiple mounting points, proceed to the **"Multiple Mounting Point Installation"** section below.



## Multiple Mounting Point Installation


### Step 1

- ❶ Locate the projector's mounting points.
- ❷ Position an appropriate number of mounting legs on the projector.

You can use any combination of three (3) or more mounting legs, depending on the number and location of the threaded inserts on your projector.



The number and placement of mounting points on projectors varies between projector manufacturers. Refer to your projector's technical specifications for the number and location of the mounting points on your specific projector.






## Attaching the Projector Plate (cont'd)

### Step 2

Insert the mounting hardware, as determined in the **"Selecting the Mounting Hardware"** section on page 9, through the leveling barrel into the threaded insert of the projector.




Do not tighten the mounting hardware at this time.



### Step 3


Raise or lower each of the mounting legs, by rotating the leveling barrels, until all of the mounting legs are at an equal height.

- Lower the mounting leg by rotating the leveling barrel counter-clockwise.
- Raise the mounting legs by rotating the leveling barrel clockwise.



### Step 4

- 1 Identify the projector's approximate front-to-back center of gravity. Place your hands on each side of the projector and gently lift it an inch from the surface on which it is resting. Carefully adjust your grip on the projector until it seems balanced from front-to-back. Mentally note the apparent center of gravity.
- 2 Identify the projector's approximate side-to-side center of gravity. Place your hands on the front and back of the projector and gently lift it an inch from the surface on which it is resting. Carefully adjust your grip on the projector until it seems balanced from side-to-side. Mentally note the apparent center of gravity.
- 3 Place the SpiroLock™ Projector Plate on top of the mounting legs with the center of the plate as close as possible to the projector's center of gravity.






## Attaching the Projector Plate (cont'd)

### Step 5

- ❶ Verify that the mounting legs are at an equal height. Return to **Step 3** if they are not at an equal height or the SpiroLock™ Projector Plate is not level.
- ❷ Verify the position of the integrated sliding M6 square nut in the mounting leg relative to a nearby slot on the SpiroLock™ Projector Plate.



If the M6 square nut is not aligned with any slot, you can use any thin implement, such as a toothpick, to nudge it into alignment.




### Step 6

Tighten the mounting screws which secure the mounting legs to the projector.



Do not overtighten the mounting screws.



### Step 7


- ❶ Attach the SpiroLock™ Projector Plate to each of the mounting legs by inserting and tightening one (1) M6 x 12mm screw through the SpiroLock™ Projector Plate into the M6 square nut on each of the mounting legs.



Do not overtighten the M6 x 12mm screw.

- ❷ Insert one (1) Barrel Cap into the end of each leveling barrel.

Proceed to the “**Attaching the Projector to the Mount**” section on page 12.





## Attaching the Projector Plate (cont'd)


### Single Mounting Point Installation

A single  $\frac{1}{4}$ -20 x  $\frac{5}{16}$ " screw must be used to attach the SpiroLock™ Projector Plate to the projector if your projector has only one mounting point.



Do not overtighten the  $\frac{1}{4}$ -20 x  $\frac{5}{16}$ " screw.

Proceed to the “Attaching the Projector to the Mount” section.



## Attaching the Projector to the Mount

### Step 1



The two (2) SpiroLock™ alignment notches must be aligned with the two (2) spindle alignment tabs.




If your projector is heavy and/or bulky, two people may be required to safely attach your projector to the SpiroLock™ Ceiling Plate.



If your projector is to be mounted higher than shoulder height, you may need to use one or more ladders to safely attach your projector to the SpiroLock™ Ceiling Plate.



Verify that the locking tab on the SpiroLock™ collar assembly is in the raised position. If the locking tab is in the lowered position, lift the locking tab and rotate the SpiroLock™ collar assembly until it retains the locking tab in the raised position.



### Step 2


- 1 Raise the projector with the SpiroLock™ Projector Plate securely attached to the SpiroLock™ Ceiling Plate.
- 2 Insert the spindle into the SpiroLock™ collar assembly.



Did the SpiroLock™ collar assembly lock into place?

If **No**, continue to press upward and rotate the projector until the SpiroLock™ collar assembly locks into place. You will see the SpiroLock™ collar assembly rotate and there will be an audible “click”. Proceed to **Step 3**.

If **Yes**, proceed to **Step 3**.






## Attaching the Projector to the Mount (cont'd)

### Step 3

Tighten the M4 x 12mm Lock-It™ screw in the SpiroLock™ collar assembly.

Proceed to the “**Alignment & Fine-Tuning**” section.



Projector not shown for clarity.

## Alignment & Fine-Tuning

- ❶ Adjust the pitch, roll, and yaw of the projector up to 6° by firmly grasping the projector with both hands and slowly tilting it forward, backward, and side-to-side.
- ❷ Make precise adjustments by placing the tip of a flat-bladed screwdriver between the projector plate and the lip of the spindle, then using gentle leverage to make any adjustments.
- ❸ Tighten the two (2) M10 x 10mm set screws in the spindle and the M6 x 25mm Lock-It™ screw in the bell housing of the SpiroLock™ mount to lock in your adjustments.




Do not overtighten the two (2) M10 x 10mm set screws.



Do not overtighten the M6 x 25mm Lock-It™ screw.

Proceed to the “**Disconnecting the Projector**” section.





## Removing the Projector

Your SpiroLock™ projector mount is designed to be quickly removed should your projector need service.




If your projector is heavy and/or bulky, two people may be required to safely attach your projector to the SpiroLock™ Ceiling Plate.



If your projector is to be mounted higher than shoulder height, you may need to use one or more ladders to safely attach your projector to the SpiroLock™ Ceiling Plate.

### Step 1

Use the M5 Security Allen Wrench to loosen the M4 x 12mm Lock-It™ screw.




### Step 2

- ① Place one hand under the projector to support it.
- ② Lift the locking tab.
- ③ While lifting the locking tab, rotate the SpiroLock™ collar assembly 15 degrees clockwise until you hear an audible “click”.



You may find it easier to lift the locking tab with the thumb of the same hand which rotates the SpiroLock™ collar assembly.

- ④ Use both hands to rotate the projector plate as shown to separate it from the SpiroLock™ collar assembly.
- ⑤ Place the projector on a soft, flat surface and disassemble the mounting legs from the projector, if necessary.







## Installing the Lock-It™ Security Barrel

Install the security barrel to help lock the projector plate to the projector:

- ❶ Determine which leveling barrel will be removed.
- ❷ Remove the mounting screw.
- ❸ Remove the leveling barrel by turning the leveling barrel counter-clockwise.
- ❹ Thread in the security barrel clockwise.
- ❺ Insert and tighten the mounting screw.
- ❻ Attach a theft deterrent device (PCB-CSL1 or padlock) through the hole that is on the security barrel.




Do not overtighten the mounting screw.




Optional security configurations (not supplied) include:

- PCB-CSL1
- Padlock (Combination or Keyed)






Counter-Clockwise



Clockwise

## Technical Specifications

All measurements are in inches.





## Warranty

### PREMIER MOUNTS LIMITED LIFETIME WARRANTY

#### What and Who is Covered by this Limited Warranty and for How Long

Premier Mounts warrants this product to be free from defects in material and workmanship for the lifetime of the original owner of this product. The limited warranty is valid only for the original purchaser of the product.

#### What Premier Mounts Will Do

At the sole option of Premier Mounts, Premier Mounts will repair or replace any product or product part that is defective. If Premier Mounts chooses to replace a defective product or part, a replacement product or part will be shipped to you at no charge, but you must pay any labor costs.

#### What is Not Covered; Limitations

PREMIER MOUNTS DISCLAIMS ANY LIABILITY FOR DAMAGE TO MOUNTS, ADAPTERS, DISPLAYS, PROJECTORS, OTHER PROPERTY, OR PERSONAL INJURY RESULTING, IN WHOLE OR IN PART, FROM IMPROPER INSTALLATION, MODIFICATION, USE OR MISUSE OF ITS PRODUCTS.

PREMIER MOUNTS DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. PREMIER MOUNTS IS NOT RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING BUT NOT LIMITED TO, INABILITY TO USE ITS PRODUCTS OR LABOR COSTS FOR REMOVING AND REPLACING DEFECTIVE PRODUCTS OR PARTS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

#### What Customers Must Do for Limited Warranty Service

If you discover a problem that you think may be covered by the warranty you MUST REPORT it in writing to the address below within thirty (30) days. Proof of purchase (an original sales receipt) from the original consumer purchaser must accompany all warranty claims. Warranty claims must also include a description of the problem, the purchaser's name, address, and telephone number. General inquiries can be addressed to Premier Mounts Customer Service at 1-800-368-9700. Warranty claims will not be accepted over the phone or by fax.

Premier Mounts  
Attn: Warranty Claim  
3130 East Miraloma Ave.  
Anaheim, CA 92806

#### How State Law Applies

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

## Disclaimer

Premier Mounts intends to make this manual accurate and complete. However, Premier Mounts makes no claim that the information contained herein covers all details, conditions or variations, nor does it provide for every possible contingency in connection with the installation or use of this product. The information contained in this document is subject to change without notice or obligation of any kind. Premier Mounts makes no representation of warranty, expressed or implied, regarding the information contained herein. Premier Mounts assumes no responsibility for accuracy, completeness or sufficiency of the information contained in this document.